

MINISTRY OF EDUCATION AND SCIENCE OF UKRAINE

ODESSA STATE ENVIRONMENTAL UNIVERSITY

*Series: Progress in Applied
Mathematics and Quantum Optics*

**ADVANCES IN QUANTUM SYSTEMS
IN CHEMISTRY, PHYSICS AND
MATHEMATICS**

Editors:

**A.V. GLUSHKOV, O.Yu. KHETSELIUS,
V.V. BUYADZHI**

KHARKIV - 2017

Advances in Quantum Systems in Chemistry, Physics and Mathematics Series: Progress in Applied Mathematics and Quantum Optics, Eds. A.V. Glushkov, O.Yu. Khetseius, V.V. Buyadzhi

Proceedings of the International Conference "Quantum systems in chemistry, physics and mathematics-2017" (QSCPM-2017), Odessa State Environmental University, Ministry of Education and Science of Ukraine. - Kh.: FOP Panov A.M., 2017. - 400 p.

ISBN 978-617-7541-44-7

The book presents the materials of papers (reports) of the International Scientific Conference "Quantum Systems in Chemistry, Physics and Mathematics" (Odessa State Environmental University, Ministry of Education and Science of Ukraine, December 1-7, 2017, Odessa, Ukraine), which contain new methods and solutions of a whole number of topical issues in the modern quantum mathematics, chemistry, physics (in particular, quantum geometry and algebra, quantum optics, spectroscopy, laser physics, dynamics of atomic and nuclear systems, atomic and molecular systems in strong external fields, new concepts and methods in quantum chemistry, physics, mathematics, relativistic effects in quantum systems, molecular structure, dynamics and spectroscopy, atomic, electronic collision, the use of the theory of quantum systems in computer science, Geo and Environmental sciences etc.).

В книгу включені матеріали праць (доповідей) Міжнародної наукової конференції «Квантові системи в хімії, фізиці та математиці» (Одеський державний екологічний університет, МОН України, 1-7 грудня, 2017, Одеса, Україна), які містять нові методи та розв'язки з низки найбільш актуальних питань сучасної квантової математики, хімії, фізики (зокрема, квантова геометрія та алгебра, квантова оптика, спектроскопія, лазерна фізика, динаміка атомних і ядерних систем, атомні і молекулярні системи в сильних зовнішніх полях, нові концепції і методи в квантовій хімії, фізиці, математиці, релятивістські ефекти в квантових системах, молекулярна структура, динаміка і спектроскопія, атомні, електронні зіткнення, застосування методів теорії квантових систем в інформатиці, науках про Землю та навколишнє середовище тощо).

It is published by the decision of the International Scientific Committee of the International Conference "Quantum Systems in Chemistry, Physics and Mathematics" (04.12.2017, Odessa, Ukraine).

UDC 539.182

ISBN 978-617-7541-44-7

© Міністерство освіти і науки України, 2017
 © Ministry of Education and Science of Ukraine, 2017
 © Одеський державний екологічний університет, 2017
 © Odessa State Environmental University, 2017
 © Автори праць, 2017
 © The authors of publications, 2017

CONTENTS

QUANTUM SYSTEMS IN ATOMIC PHYSICS AND ATOMIC AND NUCLEAR SPECTROSCOPY.....	10
OPERATOR PERTURBATION THEORY TO HYDROGEN ATOM IN A STRONG DC ELECTRIC FIELD A.V. GLUSHKOV.....	11
THE DIRAC ELECTRON: FROM QUANTUM CHEMISTRY TO HOLISTIC COSMOLOGY JEAN MARUANI.....	21
OPTICS AND SPECTROSCOPY OF COOPERATIVE ELECTRON-GAMMA-NUCLEAR PROCESSES IN HEAVY ATOMS O.Yu. KHETSELIUS.....	27
RELATIVISTIC MODEL DIRAC-FOCK APPROACH TO STUDYING Fe PLASMA EMISSION SPECTRA IN A LOW INDUCTIVE VACUUM SPARK Yu. KRUGLYAK, D. KORCHEVSKY, Yu. CHERNYAKOVA, A. IGNATENKO.....	34
ADVANCED COMPUTATIONAL APPROACH TO STUDYING RYDBERG AND AUTOIONIZATION RESONANCES IN SPECTRA OF LANTHANIDES: YTTERBIUM V B TERNOVSKY, A A SVINARENKO, V. BUYADZHI, E V TERNOVSKY, A V SMIRNOV, M. KIM.....	38
LASER MULTIPHOTON SPECTROSCOPY OF ATOM EMBEDDED IN DEBYE PLASMAS: MULTIPHOTON RESONANCES AND TRANSITIONS V.V. BUYADZHI, A.S. BELODONOV.....	46
CALCULATING THE RADIATIVE VACUUM POLARIZATION CONTRIBUTION TO THE ENERGY SHIFT OF 2P-2S TRANSITION IN PIONIC DEUTERIUM O.Yu. KHETSELIUS, L.A. VITAVETSKAYA, Y.G.CHERNYAKOVA, A.A. KUZNETSOVA D.A. KORCHEVSKY, K. VITENCHUK.....	51
AUGER-ELECTRON SPECTROSCOPY OF TRANSIENT METALS A.GLUSHKOV, A.V. TURIN, V. BUYADZHI, L. NIKOLA, V. SHPAGIN.....	55
SPECTROSCOPY OF AUTOIONIZATION RESONANCES IN SPECTRA OF HE-LIKE IONS AND ALKALI-EARTH ATOMS: NEW SPECTRAL DATA AND CHAOS EFFECT A.A. SVINARENKO, A.V. SMIRNOV, V. GRABINA, Z. ZELENTOVA.....	59
STARK EFFECT AND RESONANCES IN THE IONIZATION CONTINUUM FOR EXCITONS IN QUANTUM DOTS AND ATOMS IN AN ELECTRIC FIELD A.V. GLUSHKOV, YA.I. LEPIKH, L.LOVETT, A.V. IGNATENKO, A. GURSKAYA, A.BELODONOV.....	64

NUCLEAR ISOMERS <i>A.V. GLUSHKOV, A.V. IGNATENKO, A.A. SVINARENKO, V.B. TERNOVSKY, A. BELODONOV</i>	304
NON-LINEAR OPTICS AND SPECTROSCOPY OF ATOMIC AND LASER SYSTEMS WITH ELEMENTS OF A CHAOS <i>A. BUYADZHI, I. CHERKASOVA, A. GLUSHKOV, A. MIKHAILOV, D. MIRONENKO, E. PAVLOV, G. PREPELITSA, A. BELODONOV</i>	309
NON-LINEAR ANALYSIS OF CHAOTIC SELF-OSCILLATIONS IN NONRELATIVISTIC BACKWARD-WAVE TUBE <i>V. BUYADZHI, V. TERNOVSKY, S. BRUSENTSEVA, D. MIRONENKO, YA. KULCHYTSKY</i>	317
SIMULATION CHAOTIC DYNAMICS OF COMPLEX SYSTEMS AND DEVICES WITH USING CHAOS THEORY, GEOMETRIC ATTRACTORS, AND QUANTUM NEURAL NETWORKS <i>O. YU. KHETSELIUS, A.V. GLUSHKOV, L.B. KOVALENKO, S.V. KUZNICHENKO, A.S. BELODONOV</i>	321
STOCHASTIC DYNAMICS OF THE LASER FIELD ROTATIONAL EXCITATION FOR MOLECULES <i>D.A. KORCHEVSKY, A.V. MALAKHOV, A.V. IGNATENKO, E.L. PONOMARENKO, I.M. SHPINAREVA</i>	327
NONLINEAR DYNAMICS OF QUANTUM AND LASER SYSTEMS WITH ELEMENTS OF A CHAOS <i>A. BUYADZHI, I. CHERKASOVA, M. GURSKAYA, G.P. PREPELITSA</i>	330
PENNING AND STOCHASTIC COLLISIONAL IONIZATION OF ATOMS IN AN EXTERNAL MAGNETIC FIELD: MODEL POTENTIAL SCHEME <i>A.A. KUZNETSOVA, V. MIKHAILENKO</i>	340
NEW NONLINEAR ANALYSIS, CHAOS THEORY AND INFORMATION TECHNOLOGY APPROACH TO STUDYING DYNAMICS OF THE ERBIUM ONE-RING FIBRE LASER <i>V.B. TERNOVSKY, G.P. PREPELITSA, A. GLUSHKOV, A. BUYADZHI, V. GRABINA</i>	346
NONLINEAR DYNAMICS OF RELATIVISTIC BACKWARD-WAVE TUBE IN SELF-MODULATION AND CHAOTIC REGIME <i>V. BUYADZHI, V. TERNOVSKY, A. GLUSHKOV, O. KHETSELIUS, YA. KULCHYTSKY</i>	351
NONLINEAR DYNAMICS OF RELATIVISTIC BACKWARD-WAVE TUBE IN AUTOMODULATION AND CHAOTIC REGIME WITH ACCOUNTING THE EFFECTS WAVES REFLECTION, SPACE CHARGE FIELD AND DISSIPATION <i>V. BUYADZHI, V. TERNOVSKY, A. GLUSHKOV, YA. LEPIKH, O. KHETSELIUS, V. KLEPATSKA</i>	360
NONLINEAR CHAOTIC DYNAMICS OF ATOMIC AND MOLECULAR SYSTEMS IN AN ELECTROMAGNETIC FIELD <i>A.A. KUZNETSOVA, A. IGNATENKO, A. MAKAROVA, M. GURSKAYA, A. BUYADZHI</i>	365

NEW NONLINEAR ANALYSIS, CHAOS THEORY AND INFORMATION TECHNOLOGY APPROACH TO STUDYING DYNAMICS OF CHAIN OF QUANTUM AUTOGENERATORS <i>A. BUYADZHI, A. LAVRENKO, E. PAVLOV, O. KHETSELIUS, G. PREPELITSA, D. TIMOSHENKO</i>	370
QUANTUM SYSTEMS THEORY METHODS IN ENVIRONMENTAL AND GEOSCIENCES, INFORMATICS	375
NEW NONLINEAR CHAOS-DYNAMICAL ANALYSIS OF ATMOSPHERIC RADON ²²² RN CONCENTRATION TIME SERIES FROM BETA PARTICLES ACTIVITY DATA OF RADON MONITORS <i>O. KHETSELIUS, A. GLUSHKOV, V. BUYADZHI, Y. BUNYAKOVA, A. KULIK, N. BYKOWSZCZENKO</i>	376
REENGINEERING MODELS OF LINGUISTIC PROVIDING SOFTWARE SYSTEMS <i>S. S. VELYKODNIY, O. S. TYMOFIEIEVA</i>	385
STUDYING ENSEMBLES OF INTERVALS OF THE PARKINSONIAN TREMOR AND LOCAL POTENTIAL FLUCTUATIONS ON THE BASIS OF THE THEORY OF CHAOS <i>V. BUYADZHI, S. BRUSENTSEVA, P. ZAICHKO, K. NYAMTSU</i>	389
ON INTENSITY OF EMISSION OF THE METALS ATOMS IN A HYDROGEN-OXYGEN FLAME IN A PRESENCE OF A MAGNETIC FIELD <i>T.A. FLORKO, A.V. GLUSHKOV, V.P. KOZLOVSKAYA, G. KRAVCHENKO, Yu. LOPATKIN, A.S. SOFRONKOV</i>	394
STUDYING PHOTOKINETICS OF THE IR LASER RADIATION EFFECT ON MIXTURE OF THE CO ₂ -N ₂ -H ₂ O GASES FOR DIFFERENT ATMOSPHERIC MODELS <i>A. SVINARENKO, O. GRUSHEVSKY, V. MANSARLIYSKY, Yu. BUNYAKOVA, V. GRABINA, N. BYKOWSZCZENKO</i>	397

- Chemistry and Physics, Ser.: Progress in Theoretical Chemistry and Physics; Eds. S.Wilson, P.J.Grout, J. Maruani, G. Delgado-Barrio, P. Piecuch (Springer), 2008.-Vol.18.-P.543-560.
- 52.Glushkov A.V., Malinovskaya S., Co-operative laser nuclear processes: border lines effects// In: New projects and new lines of research in nuclear physics. Eds. G.Fazio and F.Hanappe, Singapore : World Scientific.-2003.-P.242-250.
- 53.Khetselius O.Yu., Hyperfine structure of atomic spectra.-Odessa: Astroprint, 2008.-210P.
- 54.Khetselius O.Yu., Hyperfine structure of radium// Photoelectronics.-2005.-N14.-P.83-85.
- 55.Khetselius O., Spectroscopy of cooperative electron-gamma-nuclear processes in heavy atoms: NEET effect// J. Phys.: Conf. Ser.-2012.- Vol.397.-P.012012
- 56.Khetselius O.Yu., Florko T.A., Svinarenko A.A., Tkach T.B., Radiative and collisional spectroscopy of hyperfine lines of the Li-like heavy ions and Ti atom in an atmosphere of inert gas//Phys.Scripts.-2013.-Vol.T153.-P.014037.
- 57.Khetselius O.Yu., Turin A.V., Sukharev D.E., Florko T.A., Estimating of X-ray spectra for kaonic atoms as tool for sensing the nuclear structure// Sensor Electr. and Microsyst. Techn.-2009.-N1.-P.30-35.
- 58.Glushkov A.V., Malinovskaya S.V., Gurnitskaya E.P., Khetselius O.Yu., Dubrovskaya Yu.V., Consistent quantum theory of the recoil induced excitation and ionization in atoms during capture of neutron// Journal of Physics: Conf. Series (IOP).-2006.- Vol.35.-P.425-430.
59. Xuemeng Chen, Jussi Paatero, Veli-Matti Kerminen, Laura Riuttanen, et al Responses of the atmospheric concentration of radon-222 to the vertical mixing and spatial transportation// Boreal Environment Research (Helsinki) -2016 -Vol.21- P. 299-318.
60. Jacob D.J., Prather M.J. Radon-222 as a test of convective transport in a general circulation model// Tellus-1990-Vol.42b-P.118-134.
61. Jean-Louis Pinault , Jean-Claude Baubron Signal processing of diurnal and semidiurnal variations in radon and atmospheric pressure/ A new tool for accurate in situ measurement of soil gas velocity, pressure gradient, and tortuosity //Journal of Geophysical Research-1997-Vol. 102- N b8- P.18,101-18,120.
- 62.Glushkov A.V., Khetselius O.Yu., Svinarenko A.A., Prepelitsa G.P., Energy approach to atoms in a laser field and quantum dynamics with laser pulses of different shape//In: Coherence and Ultrashort Pulse Laser Emission, Ed. by Dr. F. Duarte (InTech).-2010.-P.159-170.

Odessa State Environmental University, 15, Lvovskaya str., Odessa, Ukraine

REENGINEERING MODELS OF LINGUISTIC PROVIDING SOFTWARE SYSTEMS

The article deals with the creation of a system of concepts that form the paradigm of the reengineering of information technologies, which is necessary in the case of their evolutionary development. The scientific basis of any programming languages is linguistics, which studies laws, models and language rules. The linguistic provision of information technology addresses the construction of a software system by means of one or more (mutually agreed) programming languages, each of which is based on the rules of a particular grammar. The mathematical apparatus of generating grammars allows to describe the process of translating a program system written in one programming language into another specific language. The created paradigm allows to work with multi-level information technologies, with components that are written in different programming languages. The paradigm formulated in the article, from the scientific point of view, will be the basis of the methodology of reengineering software systems, and from the practical point of view it will be useful for system programmers who work with multi-language superstructures of software systems that acquire evolutionary development over time and improve in the process of use.

1. Introduction

Information is the base for any modern society. Without the exchange and analysis of information it is impossible not only the development of a living organism, but also its existence. There are many means of transmitting information between creatures, mostly through sensory organs. As for the humans, one of the main means of information transmission is the language, and not only its sound component (in fact information can be transmitted in written language, sign language, Braille font, etc.).

Information technology is the modern foundation for acceleration of the exchange of information among humans, the technical side of which consists of many different devices, which, in essence, are modifications of the computer. These devices also exchange information in the form of data (not only among themselves, but also with the person – the user or the operator), and, depending on the levels of data representation, the information can be presented as: binary, octal, decimal, hex codes; machine code; low and high level programming languages, etc.

2. Overview on Previous Research Activities

The scientific basis of any language (including programming languages) is linguistics, which studies laws, models and language rules. A generic linguistics [1], the founder of which was Avram Noam Chomsky, in the Soviet era, the interpretation of "A.N. Khomsky", was a special branch of linguistics that should be applied to the structure of programming languages, which created a revolution in linguistics [2, 3].

By the way of the assigning of true chains, formal grammars are divided into generative and recognizable. The generators include the grammars in which one can construct any valid chain with an indication of its structure and it is impossible to construct any wrong chains. For the first time, the notion of generative (generative) grammar was proposed by A. N. Chomsky [4]. Recognition grammar is a grammar that allows you to establish the fidelity of an arbitrarily selected chain, and, if it is correct, to find out its structure.

The linguistic provision of information technology addresses the construction of a software system by means of one or more

(mutually agreed) programming languages, each of which is based on the rules of a particular grammar [5].

Formal languages include, in particular, artificial languages for communication between the operator and the computer (programming languages) [6].

The purpose of the study is to create a system of concepts that forms the paradigm of information technology reengineering, which will allow working with multi-level software systems whose component parts are written in different programming languages.

3. Statement of the problem

To designate the description of a formal language, it is necessary, first of all, to indicate the *alphabet*, that is, a collection of objects called symbols (or letters), each of which can be reproduced in an unlimited number of instances, and second to set the formal grammar of language, that is, list the rules by which the characters are compiled into the sequences belonging to a specific language.

Any programming language is a set of chains in some final alphabet. In linguistics, instead of the term "alphabet", the term "dictionary" is used because the elements from which it is composed are word forms [7]. At the same time, the chain over the dictionary is considered as a phrase or sentence.

Note that each symbol of the alphabet is considered inseparable in the sense that when constructing chains, its graphic elements (parts of characters) are never used, and any sequence of characters uniquely represents a certain chain.

In practice, this requirement is achieved, for example, by setting a "space" (a standard length gap) between the symbols. This "space" exceeds the length of any of the spaces encountered inside the characters of the alphabet.

Rules of formal grammar should be considered as "products" (exit rules) - elementary operations, which, if applied in a definite sequence to the original chain (axioms), generate only the right chains. The

very sequence of rules used in the process of generating a chain is its rendering. The language thus defined in that way is a formal system. Known examples of formal systems are logical calculations (statements, predicates) that relate to the sections of mathematical logic.

4. Materials and research results

Generative grammar or, in short, grammar is basically an ordered set:

$$G = \langle A, \Psi, \varepsilon, Z \rangle, \quad (1)$$

where $A = \{a_1, a_2, \dots, a_n\}$ - base terminal alphabet; Ψ - auxiliary (after-terminal) alphabet, the characters of which are indicated by lowercase Greek letters; $\varepsilon (\varepsilon \in \Psi)$ - initial (after-terminal) character; Z - the final system of variables:

$$Z = \{u_i \rightarrow v_i \mid i = 1, 2, \dots, k\}, \quad (2)$$

where u_i - is the chain; $v_i \in \delta(v)$, where $\delta(v)$ - free semigroup over the combined alphabet Θ :

$$\Theta = \langle A \cup \Psi \rangle. \quad (3)$$

In other words, the characters from the main alphabet A are the primary units of the language that is defined. Symbols of the alphabet Ψ are *meta-changeable* and used in the presentation of the correct chains (in natural languages, such variables are grammatical classes: noun, verb, etc.).

ε - a meta-changeable axiom from which all the correct chains are built (in the natural languages the grammatical class "sentence" corresponds to the axiom).

Z - a layout of grammar consisting of products (the rules of presentation - the grammatical rules of the determined language).

For example, the generative grammar is:

$$G_0 = \langle \{a, b, c\}, \{\alpha, \beta, \chi\}, \varepsilon, Z_0 \rangle, \quad (4)$$

and Z_0 has a set of rules:

$$Z_0 = \begin{cases} \varepsilon \rightarrow abc, \\ \varepsilon \rightarrow b, \\ \varepsilon \rightarrow \alpha\alpha, \\ abc \rightarrow c. \end{cases} \quad (5)$$

Definition of the language $L(G)$, produced by generative grammar G , associated with concept of "rendering".

Assuming x, y are chains belonging to free semigroup $\delta(v)$.

Chain y is direct output from chain x in grammar G :

$$x \xrightarrow[G]{\Rightarrow} y \text{ or } x \Rightarrow y \text{ (where } G \text{ is meant)}, \quad (6)$$

if there is a product $u \rightarrow v$ in a scheme Z of the given grammar:

$$\begin{cases} x = x_1 u x_2, \\ y = x_1 v x_2; \end{cases} \quad (7)$$

where $x_1, x_2 \in \delta(v)$.

Then the chain y is obtained as a result of applying outcome $u \rightarrow v \in Z$ to a chain x , which means the replacement in the chain x of the selected entry on the left part u of the supplied product to its right part v .

For example, in grammar G_0 :

$$bc \Rightarrow c \Rightarrow b\alpha\alpha c, \quad abcba \Rightarrow cba, \dots (8)$$

The chain y can be derived from chain x belonging to a grammar G , $x \xrightarrow[G]{\Rightarrow} y$ or $x \Rightarrow y$

which is similar to (6) if chains x and y coincided or there is such a sequence of chains z_0, z_1, \dots, z_k , that

$$z_0 = x, \quad z_k = y \quad \wedge \quad \forall i (1 \leq i \leq k) \quad z_{i-1} \Rightarrow z_i. \quad (9)$$

The sequence of chains $Q = (z_0, z_1, \dots, z_k)$ is called "rendering" of the chain y from chain x in grammar G .

For example, in grammar G_0 $\varepsilon \Rightarrow acc$, where progression is the result of rendering chain acc from chain ε :

$$\begin{aligned} & \langle \varepsilon \Rightarrow abc; abc \Rightarrow \alpha\alpha c \mid b \rightarrow \varepsilon; \\ & \alpha\alpha c \Rightarrow aabcc \mid \varepsilon \rightarrow abc; \\ & aabcc \Rightarrow acc \mid abc \rightarrow c \rangle. \quad (10) \end{aligned}$$

It should be added that at each step of the rendering, you can choose any of the products that can be applied at the moment. This means that the sequencing of the use of products in grammar is arbitrary and any products allowed to be applied after another, but within a system of rules.

Thus, the notion of generating grammar is fundamentally different from the notion of "normal algorithm", in which substitutions are of a definite character and are strictly executed in advance of the specified sequence.

Rendering $x \xrightarrow[G]{\Rightarrow} y$ could be considered as

complete if $y \in \delta(A)$ - that is the chain y consists of terminal characters. Any complete rendering ends with use of the products if their right-hand sides are terminal chains. Specified products we will call "final products" of the given grammar.

If $x \xrightarrow[G]{\Rightarrow} y$ and $y \notin \delta(A)$, and there is no rules

in system Z that could be applied to the chain y , then rendering of chain y from chain x in grammar G is called *dead end*.

For example: rendering that generated in (10) is complete in grammar G_0 , acc is the end product of grammar G_0 .

And the following rendering:

$$\begin{aligned} & \langle aabcbcc \Rightarrow \alpha\alpha abc \mid abc \rightarrow \varepsilon; \\ & \alpha\alpha abc \Rightarrow \alpha\alpha c \mid abc \rightarrow c; \\ & \alpha\alpha c \Rightarrow \alpha\alpha\alpha c \mid \varepsilon \rightarrow \alpha\alpha \rangle \quad (11) \end{aligned}$$

is the dead end rendering of the chain $\alpha\alpha\alpha c$ from the chain $aabcabc$ in grammar G_0 . Now let's take a look at generative grammar $G = (A, \Psi, \varepsilon, Z)$ defines the language that matches it. The chain $x \in \delta(A)$ will be true if there is at least one complete rendering of the chain from axiom ε in grammar G . In other words the chain x is true if: $x \in \delta(A)$ – chain x consists of terminal characters; $\varepsilon \xrightarrow{G} x$ – such rendering of chain x from axiom ε exists. Variety of all true chains in grammar G creates a language $L(G)$ that is generated by grammar G . For example, grammar G_0 generates following language:

$$L(G_0) = \{x^n y x^n \cup y^m x y^m | n, m = 0, 1, 2, \dots\} \quad (12)$$

Consequently, each grammar $G = (A, \Psi, \varepsilon, Z)$ clearly corresponds to the language $L(G)$ generated by this grammar. However, this correspondence is not isomorphic: the same language can be generated by various grammars. This allows you to apply the equivalence relation to the endless set of grammars. Grammars G and G' can be considered to be equivalent ($G \leftrightarrow G'$) if $L(G) = L(G')$ that is, grammar G and G' generate one language. For example, grammar:

$$G_1 = (\{a, b, c\}, \{\varepsilon\}, \varepsilon, Z_1), \quad (13)$$

the scheme of which has following set of rules:

$$Z_1 = \begin{cases} \varepsilon \rightarrow abc, \\ \varepsilon \rightarrow b, \\ \varepsilon \rightarrow c, \end{cases} \quad (14)$$

will generate the language $L(G_1)$, which coincides with language $L(G_0)$ and thereafter means that $G_0 \leftrightarrow G_1$.

5. Conclusion

Summing-up the outlined content, we will note that generative and grammar can be widely used in considering the linguistic provision of software systems. Particularly important, the generating grammar tool gains in the event of the necessary reengineering of the program code, which is written in different programming languages.

The paradigm formulated in the article, from the scientific point of view, will be the basis of the methodology of reengineering software systems, and from the practical point of view it will be useful for system programmers who work with multi-language superstructures of software systems that acquire evolutionary development over time and improve in the process of use.

References

1. Rudnev V. P., "Heneratyvnyaya linyvystyka" (Slovar' kul'tury XX veka) [Online]. Available: http://www.gumer.info/bibliotek_Buks/Culture/Rudnev/Dict/04.php.
2. Noam Chomsky, "Logical Syntax and Semantics: Their Linguistic Relevance" [Online]. Available: <https://chomsky.info/wp-content/uploads/195503.pdf>.
3. Noam Chomsky, "Three Models for the Description of Language" [Online].
4. wiseGEEK, "What is Generative Grammar?" [Online]. Available: <http://www.wisegeek.com/what-is-generative-grammar.htm>.
5. Serhiy Horelov, "Evrystychnyy analiz hramatyky" (Evrystychnyy analiz bud'yakoyi movy).
6. Hlushkov V. M., Tseytlyn H. E., Yushchenko E. L., "Algebra. Yazyky. Prohrammyrovanye". Kyiv, USSR: Nauk dumka, 1974. 328 p.
7. Fedorenko O. F., Sukhorol'ska S. M., Ruda O. V., "Osnovy linyvystychnykh doslidzhen = Fundamentals of Linguistic Research". Lviv, Ukraine: Tsentr, I. Franko's LNU, 2009. 296 p.

UDC 681.320

V. BUYADZHI, S. BRUSENTSEVA, P. ZAICHKO, K. NYAMTSU

Odessa National Maritime Academy, Odessa, Ukraine, 4, Didrikhsona, Odessa, Ukraine
Odessa State Environmental University, 15, Lvovskaya str., Odessa, Ukraine

STUDYING ENSEMBLES OF INTERVALS OF THE PARKINSONIAN TREMOR AND LOCAL POTENTIAL FLUCTUATIONS ON THE BASIS OF THE THEORY OF CHAOS

The work is devoted to the use of methods of chaos theory to characterize the nonlinear dynamics of neurophysiological systems and identify the presence of chaotic elements. The data of the studying the Parkinsonian tremor interval ensembles and the corresponding fluctuations of the local potential are presented.

1. Introduction.

The task of studying the dynamics of chaotic dynamical systems arises in many areas of science and technology. We are talking about a class of problems of identifying and estimating the parameters of interaction between the sources of complex (chaotic) oscillations of the time series of experimentally observed values. Such problems arise in physics, biology, medicine, neuroscience, geophysics, engineering, etc. Many studies in the cited and other fields of science and technique have appeared, where a chaos theory was applied to a great number of dynamical systems [1-12]. These studies show that chaos theory methodology can be applied and the short-range forecast by the non-linear prediction method can be satisfactory. Time series of the dynamical variables are however not always chaotic, and chaotic behaviour must be examined for each time series. In series of papers it has been developed an effective version of using a chaos theory method and non-linear prediction approach to studying chaotic behaviour of the different dynamical systems. In our opinion, using these methods has very attractive perspectives in medicine and physiology (neuro-physiology). As example, let us underline that an ability to provide interaction between the different areas of the brain by using a multi-channel electroencephalograms helps determine the

location of the foci of abnormal activity in brain of patients with epilepsy. Many diseases of the brain, including epilepsy, Parkinson's disease, are associated with abnormal synchronization large groups of neurons in the brain. Particular attention is paid to a non-linear signals as obvious is a typicality of a chaotic behavior of nonlinear systems.

This paper is devoted to an employing a variety of techniques for characterizing dynamics of the nonlinear neurophysiological systems identifying the presence of chaotic elements. To analyze measured time histories of the neurophysiological system responses the phase space of these systems was reconstructed by delay embedding. Here we also present the numerical results regarding the Parkinsonian tremor interval ensembles of a few patients and the corresponding fluctuations of the local potential. To implement this program, we follow the procedure set out in detail in [10-12].

2. Method: Testing for chaos in time series

2.1. Data

Many diseases of the nervous system, including epilepsy and Parkinson's disease associated with abnormal synchronization large groups of neurons in the brain. A sign

Наукове видання

Редактори:

Глушков Олександр Васильович, д.ф.-м.н., проф.

Хецеліус Ольга Юрївна, д.ф.-м.н., проф.

Буяджи Василь Володимирович, к.ф.-м.н., доц.

**ДОСЯГНЕННЯ В КВАНТОВИХ СИСТЕМАХ
У ХІМІЇ, ФІЗИЦІ ТА МАТЕМАТИЦІ**

Серія: Прогрес у прикладній математиці та квантовій оптиці

**Збірник матеріалів праць (доповідей)
Міжнародної конференції «Квантові системи
у хімії, фізиці та математиці»
(грудень 1-7, 2017,
Одеський державний екологічний університет,
Міністерство освіти та науки України)**

Англійською мовою

Надруковано з готового оригінал-макета

Підп. до друку 06.12.2017. Формат 60x84/16.
Гарнітура Таймс. Друк цифровий. Папір офсетний.
Обсяг: 25,75 ум.-друк. арк. Наклад 100 прим. Замовлення № 01\12\17.

Видавець: ФОП Панов А.М.
Свідоцтво серії ДК №4847 від 06.02.2015 р.
м. Харків, вул. Жон Мироносиць 10, оф. 6,
тел. +38(057)714-06-74, +38(050)976-32-87
copy@vlavke.com.ua

Одеський державний екологічний університет
65016, Одеса, вул. Львівська, 15.